- 2 - Art Unit: 1743

Serial No.: 10/611,416

Conf. No.: 1935

In the Claims

Please replace all prior versions, and listings, of claims in the application with the following list of claims: 1-8. (Canceled) The method of claim 8 wherein the surface comprises A method of 9. (Currently amended) detecting sulfate comprising: providing a sample comprising sulfate; converting at least a portion of the sulfate to sulfur dioxide; and continuously determining the sulfur dioxide, wherein the at least a portion of the sulfate is converted to sulfur dioxide by passing the sample over a surface comprising chromium carbide. The method of claim 8 wherein the surface comprises A method of 10. (Currently amended) detecting sulfate comprising: providing a sample comprising sulfate; converting at least a portion of the sulfate to sulfur dioxide; and continuously determining the sulfur dioxide, wherein the at least a portion of the sulfate is converted to sulfur dioxide by passing the sample over a surface comprising a chromium salt. 11-38. (Canceled) The method of claim 38 wherein A method of detecting sulfate 39. (Currently amended) comprising: passing a sample comprising sulfate over a surface, the surface comprising a transition metal and being at an elevated temperature; reducing at least a portion of the sulfate to sulfur dioxide; and continuously determining at least a portion of the sulfur dioxide is determined at a rate of more than one reading per second.

Art Unit: 1743

- 3 -

Serial No.: 10/611,416 Conf. No.: 1935


40. (Currently amended) The method of claim 2139 wherein the at least a portion	of the
sulfur dioxide is determined at a rate of about 10 times per second.	
41-42. (Canceled)	
43. (Currently amended) The method of claim 21 wherein the surface comprises	A method
of detecting sulfate comprising:	
passing a sample comprising sulfate over a surface comprising chromium carb	ide <u>, the</u>
surface being at an elevated temperature;	
reducing at least a portion of the sulfate to sulfur dioxide; and	•
continuously determining at least a portion of the sulfur dioxide.	
44. (Canceled) 45. (Currently amended) The method of claim 21 wherein the surface comprises	A method
of detecting sulfate comprising:	
passing a sample comprising sulfate over a surface comprising a metallic chro	mium
wool, the surface being at an elevated temperature;	•
reducing at least a portion of the sulfate to sulfur dioxide; and	
continuously determining at least a portion of the sulfur dioxide.	
46-62. (Canceled)	
63. (Currently amended) The method of claim 62 wherein the sulfur dioxide is de	termined
A method of detecting sulfate comprising:	
passing air comprising particulate matter across a heated surface comprising c	nromium,
the particulate matter comprising sulfate;	
reducing at least a portion of the sulfate to sulfur dioxide; and	
determining sulfur dioxide via a pulse fluorescence sulfur dioxide detector.	

Art Unit: 1743

Serial No.: 10/611,416

Conf. No.: 1935

64-73. (Canceled)



- 4 -

Serial No.: 10/611,416 - 5 - Art Unit: 1743

Conf. No.: 1935

92. (New) The method of claim 10 wherein at least 90% of the sulfate is converted to sulfur dioxide.

93. (New) The method of claim 39 wherein the at least a portion of sulfur dioxide is determined via pulsed fluorescence detection.

94. (New) The method of claim 39 wherein determining comprises quantifying the at least a portion of the sulfur dioxide.

95. (New) The method of claim 39 wherein at least 50% of the sulfate is reduced to sulfur dioxide.

96. (New) The method of claim 39 wherein at least 90% of the sulfate is reduced to sulfur dioxide.

97. (New) The method of claim 43 wherein the sulfur dioxide is determined via pulsed fluorescence detection.

98. (New) The method of claim 43 wherein determining comprises quantifying the sulfur dioxide.

99. (New) The method of claim 43 wherein at least 50% of the sulfate is reduced to sulfur dioxide.

100. (New) The method of claim 43 wherein at least 90% of the sulfate is reduced to sulfur dioxide.

101. (New) The method of claim 45 wherein the sulfur dioxide is determined via pulsed fluorescence detection.

Serial No.: 10/611,416

Conf. No.: 1935

The method of claim 45 wherein determining comprises quantifying the sulfur 102. (New) dioxide.

The method of claim 45 wherein at least 50% of the sulfate is reduced to sulfur 103. (New) dioxide.

The method of claim 45 wherein at least 90% of the sulfate is reduced to sulfur 104. (New) dioxide.

The method of claim 63 wherein determining comprises quantifying the sulfur 105. (New) dioxide.

The method of claim 63 wherein at least 50% of the sulfate is reduced to sulfur 106. (New) dioxide.

The method of claim 63 wherein at least 90% of the sulfate is reduced to sulfur 107. (New) dioxide.

The method of claim 63 wherein the sulfur dioxide is determined at a rate of more 108. (New) than one reading per minute.

The method of claim 63 wherein the sulfur dioxide is determined continuously. 109. (New)

The method of claim 63 wherein the heated surface comprises stainless steel. 110. (New)

The method of claim 74 wherein determining comprises quantifying the sulfur 111. (New) dioxide.

The method of claim 74 wherein at least 50% of the sulfate is reduced to sulfur 112. (New) dioxide.

Serial No.: 10/611,416 - 7 - Art Unit: 1743

Conf. No.: 1935

113. (New) The method of claim 74 wherein at least 90% of the sulfate is reduced to sulfur dioxide.

114. (New) The method of claim 74 wherein the sulfur dioxide is determined at a rate of more than one reading per minute.

115. (New) The method of claim 74 wherein the sulfur dioxide is determined continuously.